



19507A Mobile Saline AND Medication Cabinet

WWW.OTEINTERNATIONAL.COM
 6695 CR 4628
 Athens, TX 75752
 sales@oteinternational.com



	Med	Saline	Outside Dimensions
Height	4"	4"	22.00"
Width	10.5"	10"	20.63"
Depth	10.7"	10.7"	19.63"
VDC	11-15 VDC		
Amps	4.5 to 15 (peak)		
Airflow Requirements: 85CFM			

Product Overview

- **Two concise** temperature controlled storage areas one for saline and one for medications
- **Functional** in mobile, temporary or stationary environments
- **Reliable, Robust and Low Maintenance Solid-State** heat pump technology
- **Compression locks** for a airtight seal
- **High tech insulation and thermoelectric proportional controlled methodology**
- **Manufactured in U.S.A.**

Electrical

Unit operates at 12 or 24 VDC. Peak power Consumption is dependent upon model and operating environment but typical power consumption at normal ambient temperatures (90F to 30F) is 50-80% of peak. Unit can be equipped with optional low voltage shutdown. (when voltage is restored the unit automatically restarts)

Temperature Control

Heating and cooling is accomplished using high efficiency thermoelectric heat pump technology. The temperature control boards use a proportional control program to maintain minimal temperature variation inside the unit. Internal temperature is preset but custom temperature settings are available. Insulation is state of the art vacuum and PU panels that provide a barrier of maximum efficiency from external temperatures.

Design

Products contain no CFC's nor harmful contaminants requiring only standard tools for installation. Unit is field serviceable with the field service guide. Unit can be configured to operate on 120/220 VAC with optional DC power conversion. OTE engines are designed and manufactured to work day in and day out in the toughest conditions.

* Specification for reference only and are subject to change without notice.